ITEM NO. 3781207 / MODEL NO. 5072550000 **HAMPTON[™] R**

72" x 42" x 23-1/2", Acrylic, Swirl-Way® Whirlpool

FEATURES

- · High gloss, easy-to-clean acrylic with fiberglass reinforcement
- Whirlpool hydromassage system uses fully controllable, high-pressure back and body jets for complete muscle relief
- · Hydro-V back jet system with back and body jets
- · All jets are directionally and flow adjustable
- · Includes one pillow
- · Rectangular model with end drain (left- or right-hand installation)
- Pre-leveled legs for easy installation
- · Integrated dual armrests for bather's comfort
- Two decorative handles
- · Spacious bathing well designed for one-person comfort
- · 10-year limited warranty on acrylic
- Installation: Drop-In or Alcove
- · Available in White



COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS	
5072550000	72' x 42' x 23-1/2' Rectangular Swirl-Way® Whirlpool. Drain not included.	UPC ® USPC US	
ACCESSORIES			
CAB-	Cable Overflow Drain (White — 1330, Chrome — 1335, Everbrass — 1336, Brushed Nickel — 1337, Oil Rubbed Bronze — 1338, Matte Black — 1339)		
TIP-	Tip Toe Overflow Drain (Chrome — 1335, Everbrass — 1336, Brushed Nickel — 1337, Oil Rubbed Bronze — 1338, Matte Black — 1339)		
SWAPOO	Nailing Flange Kit (includes 14' PVC nailing flange, tacky tape and installation instructions)		




72" x 42" x 23-1/2", Acrylic, Swirl-Way® Whirlpool


SPECIFICATIONS

MATERIAL	Acrylic, fiberglass reinforced
CONSTRUCTION	Self contained, pre-plumbed whirlpool bath system mounted on pre-leveled base.
ELECTRICAL REQUIREMENTS	One 120 volt, 20 amp GFCI dedicated circuit. Optional heater: separate 120 volt, 20 amp dedicated circuit.


SOAKING DEPTH	17-3/4'
NUMBER OF JETS	14
WATER CAPACITY	60 gal. (min.) / 80 gal. (max)
FLOOR LOADING WEIGHT	47 lbs. sq.ft.
SHIPPING WEIGHT	Model 5072550000 - 175 lbs. (79 kg)
WHIRLPOOL PUMP	9 amp
WARRANTY	Acrylic - 10-Year

TECHNICAL INFORMATION





Note: these dimensions are nominal and subject to change without notice.



NOTES:

- 1. Pump locations are shown for clarity.
- 2. Required pump motor access is 20" W x 15" H.
- 3. Measurements may vary 1/4" (+/-)
- 4. If a factory installed nailing flange is added to a unit, add 1/8" to each side flanged.

- 39" -(991 mm)

- 5. Removable apron is not available for this unit.
- 6. These dimensions are nominal and subject to
- change without notice.

