

RESTORE™ ACR WALK-IN BATHS



51 1/2" X 30" X 40"

FEATURES

- Acrylic construction with fiberglass reinforcement
- 17" high, ADA compliant seat
- Replaces standard size tub with right or left hand drain
- Fits through a standard 32" bathroom doorway
- Available in Bathtub, Whirlpool, Air Bath, Combination Whirlpool and Air Massage Bath and MicroDerm™ Therapeutic Baths (see options available below)
- Simplified installation procedure
- Custom designed, ergonomic door handle
- Durable one-inch steel frame with adjustable leveling leg
- Removable front and end panels for complete access to operating system
- Cable operated drain included in White
- Available in White



MODEL #	DESCRIPTION	CABLE DRAIN - WHITE	WHIRLPOOL JETS	AIR JETS	MICROBUBBLE PORTS	ON/OFF KEYPAD	MULTIFUNCTION KEYPAD	INLINE HEATER	CHROMATHERAPY COLOR LIGHT SYSTEM	HEATED SEAT & BACKREST MODEL: ACR151	EXTENSION BOX MODEL: ACR-001	END PANEL MODEL: ACR-002	NAILING FLANGE KIT MODEL: SWAPOOL
80905	Restore™ ACR RH Whirlpool The Essentials	STD	12	-	-	STD	-	STD	N/A	OPT	OPT	OPT	OPT
81905	Restore™ ACR LH Whirlpool The Essentials	STD	12	-	-	STD	-	STD	N/A	OPT	OPT	OPT	OPT
809051	Restore™ ACR RH Whirlpool Comfort Package	STD	12	-	-	-	STD	STD	STD	OPT	OPT	OPT	OPT
8195	Restore™ ACR LH Whirlpool Comfort Package	STD	12	-	-	-	STD	STD	STD	OPT	OPT	OPT	OPT
8290	Restore™ ACR RH Bath	STD	-	-	-	-	-	N/A	N/A	OPT	OPT	OPT	OPT
8390	Restore™ ACR LH Bath	STD	-	-	-	-	-	N/A	N/A	OPT	OPT	OPT	OPT
8490	Restore™ ACR RH Air Bath	STD	-	30	-	-	STD	N/A	STD	OPT	OPT	OPT	OPT
8590	Restore™ ACR LH Air Bath	STD	-	30	-	-	STD	N/A	STD	OPT	OPT	OPT	OPT
8690	Restore™ ACR RH Combination	STD	12	30	-	-	STD	STD	STD	OPT	OPT	OPT	OPT
8790	Restore™ ACR LH Combination	STD	12	30	-	-	STD	STD	STD	OPT	OPT	OPT	OPT
8890	Restore™ ACR RH MicroDerm™	STD	-	-	1	STD	-	N/A	N/A	OPT	OPT	OPT	OPT
8990	Restore™ ACR LH MicroDerm™	STD	-	-	1	STD	-	N/A	N/A	OPT	OPT	OPT	OPT

RESTORE™ ACR




WALK-IN BATHS



51 1/2" X 30" X 40"

SPECIFICATIONS

MATERIAL	Acrylic, fiberglass reinforced	
CONSTRUCTION	Self contained, pre-plumbed and mounted on a steel frame with adjustable leveling legs	
ELECTRICAL REQUIREMENTS	Whirlpools:	Two dedicated 120 volt, 20 amp GFCI protected circuits
	Air Bath & Microderm:	One dedicated 120 volt, 20 amp GFCI protected circuit
	Combination:	Three dedicated 120 volt, 20 amp GFCI protected circuits
WATER CAPACITY	50 gal. (min.) / 70 gal. (max.) with bather	
FLOOR LOADING WEIGHT	450 lbs.	
NUMBER OF JETS	WP 12 - Whirlpool and Combination AIR 30 - Air bath and Combination	

SHIPPING WEIGHT	210 lbs. - Bathtub 230 lbs. - Air Massage Bath 235 lbs. - Whirlpool and MicroDerm 255 lbs. - Combination
WHIRLPOOL PUMP	120 volt, 7 amp
AIR BATH BLOWER	120 volt, 600 watt with heating element
WARRANTY	Operating system - 5 year warranty Shell - 10 year warranty Door seal - Lifetime warranty
CERTIFICATIONS	  

TECHNICAL INFORMATION

Note: these dimensions are nominal and subject to change without notice.

