MANSFIELD®

Round Front, Vitreous China, Two-Piece Toilet

FEATURES

- · 3-bolt SmartFasten™ tank-to-bowl connection
- 1.6 gpf / 6.0 lpf low water consumption
- · Round front bowl
- 2" flush tower
- · Fluidmaster® anti-siphon pilot fill valve
- 12" rough-in
- · Model 40 chrome-plated, plastic trip lever
- · Cover lock tank lid
- · 2" glazed trapway
- · The Mansfield® Limited Lifetime Warranty
- · Available in White



COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS		
130-165	Round front, two-piece toilet			
130	Round front, toilet bowl only. Less toilet seat. Specify color.			
165	Tank and cover only with left hand, front-mount, chrome-plated, plastic trip lever. Fluidmaster® anti-siphon pilot fill valve. Cover lock. Less supply.	c ®		
TANK TRIM & REPLACEMENT PARTS				
40	Trip lever - chrome-plated, plastic trip lever, left hand			
211-1112	Flush tower			
400A	Fluidmaster® anti-siphon pilot fill valve			
630-0030	Replacement flush valve seal			
165-LID	Tank lid (cover lock)			
Part # 001238891	Locking hardware for cover lock tanks			

130-165

ALTO®

MANSFIELD®

Round Front, Vitreous China, Two-Piece Toilet

SPECIFICATIONS

MODEL #	DESCRIPTION	CODES/STANDARDS
130-165	Round front (1.6 gpf / 6.0 lpf) two-piece toilet	C ®

MATERIAL	Vitreous China
WATER PRESSURE RANGE	20 to 80 PSI
FLUSH SYSTEM	2" Flush Tower
WATER USAGE	1.6 gpf / 6.0 lpf
WATER SURFACE AREA	8" X 9"
ROUGH-IN	12"
MAP RATING	800 grams

TRAP DIAMETER	2"
TRAP SEAL	2-5/8"
SHIPPING WEIGHT	Model 130 - 46 lbs. (21 kg) Model 165 - 34 lbs. (15 kg)
WARRANTY	Vitreous China - Limited Lifetime Tank Trim - Limited One Year


TANK OPTIONS

IANN UTIIUNS		
160	Standard 1.6 gpf configuration: 2" flush tower, Fluidmaster® anti-siphon pilot fill valve, left hand, chrome trip lever.	
160RH	Variation of model 160, with right hand trip lever.	
165	Variation of model 160, with cover lock.	
170	Variation of model 160, with tank liner.	
172	Variation of model 160, with 2" flapper flush valve and chrome trip lever.	
173	Variation of model 160, with 2" flapper flush valve and color-match trip lever.	
173RH	Variation of model 173, with right hand trip lever.	
174	Variation of model 173, with tank liner.	
175	Variation of model 160, with cover lock and tank liner.	
180	Variation of model 160, with color-match trip lever.	
190	Variation of model 160, with color-match trip lever and tank liner.	
1	T. Control of the con	

Variation of model 160, with 14" rough-in.

TECHNICAL INFORMATION

Note: these dimensions are nominal and subject to change without notice.



Fixture performance and specifications meet or exceed ASME A112.19.2/CSA B45.1 standards, and other state and local codes.