

# 131-160RH ALTO®

# MANSFIELD®

Round Front, Vitreous China, Two-Piece Toilet

## FEATURES

- 3-bolt SmartFasten™ tank-to-bowl connection
- 1.6 gpf / 6.0 lpf low water consumption
- Round front bowl
- 2' flush tower
- Anti-siphon ballcock
- 10" rough-in
- Model 40RH chrome-plated, plastic trip lever
- 2' glazed trapway
- The Mansfield® Limited Lifetime Warranty
- Available in White



**MODEL 131-160RH**

Toilet seat not included



ROUND

## COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS
<b>131-160RH</b>	Round front, two-piece toilet.	
<b>131</b>	Round front, toilet bowl only. Less toilet seat. Specify color.	
<b>160RH</b>	Tank and cover only with right hand, front-mount, chrome-plated, plastic trip lever. Less supply.	
<b>TANK TRIM &amp; REPLACEMENT PARTS</b>		
<b>40RH</b>	Trip lever - chrome-plated, plastic trip lever, right hand	
<b>211-1112</b>	Flush tower	
<b>08ULF-1112</b>	Anti-siphon ballcock	
<b>630-0030</b>	Replacement flush valve seal	
<b>160-LID</b>	Tank lid	



# 131-160RH ALTO®



Round Front, Vitreous China, Two-Piece Toilet

## SPECIFICATIONS

MODEL #	DESCRIPTION	CODES/STANDARDS
131-160RH	Round front (1.6 gpf / 6.0 lpf) two-piece toilet	

MATERIAL	Vitreous China
WATER PRESSURE RANGE	20 to 80 PSI
FLUSH SYSTEM	2" Flush Tower
WATER USAGE	1.6 gpf / 6.0 lpf
WATER SURFACE AREA	8' X 9'
ROUGH-IN	10'
MAP RATING	800 grams

TRAP DIAMETER	2'
TRAP SEAL	2-1/4'
SHIPPING WEIGHT	Model 131 - 47 lbs. (21 kg) Model 160RH - 34 lbs. (15 kg)
WARRANTY	Vitreous China - Limited Lifetime Tank Trim - Limited One Year

TANK OPTIONS		TECHNICAL INFORMATION
		<b>Note:</b> these dimensions are nominal and subject to change without notice.
160	Standard 1.6 gpf configuration: 2" flush tower, anti-siphon ballcock, left hand, chrome trip lever.	
160RH	Variation of model 160, with right hand trip lever.	
161	Variation of model 160, with Fluidmaster® anti-siphon pilot fill valve.	
165	Variation of model 160, with cover lock.	
170	Variation of model 160, with tank liner.	
172	Variation of model 160, with Fluidmaster® anti-siphon pilot fill valve, 2" flapper and chrome trip lever.	
173	Variation of model 160, with Fluidmaster® anti-siphon pilot fill valve, 2" flapper and color-match trip lever.	
173RH	Variation of model 173, with right hand trip lever.	
174	Variation of model 173, with tank liner.	
175	Variation of model 160, with cover lock and tank liner.	
180	Variation of model 160, with color-match trip lever.	
181	Variation of model 160, with Fluidmaster® anti-siphon pilot fill valve and color-match trip lever.	
190	Variation of model 160, with color-match trip lever and tank liner.	



Fixture performance and specifications meet or exceed ASME A112.19.2/CSA B45.1 standards, and other state and local codes.