

Cylinders

Wall Mounted • Wet Location Listed **PROGRESS LED**

Description:

3" Wall Mount Downlight Cylinder. DarkSky approval ensures focused, downward illumination that minimizes light pollution, enhancing the night sky while beautifully lighting outdoor spaces.

Specifications:

- Clear Glass Lens
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" recessed outlet box: 4.4375 in W, 4.4375 in ht., 1.015 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied
- Yes, per photometry (not registered with IDA)

Performance:

Number of Modules	1
Input Power	12 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	987/75 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	CSA Listed Wet Location Listed
	Meets California Title 24 JA8-2016
	DarkSky Approved

P563000-031-30K



Dimensions:

Width: 4-1/2 in
 Depth: 5-1/2 in
 Height: 5-5/8 in
 H/CTR: 3 in

Dimming Notes:

P563000-031-30K is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVELV-300P

Lutron_Caseta Wireless

Leviton_SureSlide 6672

Lutron_Ariadni AYCL-153P

Lutron_Toggler TGCL-153PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P563000-031-30K