

137-3173 (K13700073)

ALTO® 1.28



Elongated Front ADA*, SmartHeight, Vitreous China, Two-Piece Toilet

FEATURES

- 3-bolt SmartFasten tank-to-bowl connection
- 1.28 gpf / 4.8 lpf high efficiency water consumption
- Uses 20% less water than conventional toilets
- Elongated front SmartHeight bowl
- 3-2" hybrid flapper flush valve
- Fluidmaster® anti-siphon pilot fill valve
- 12" rough-in
- Model 31 color-match, plastic trip lever
- 2" glazed trapway
- The Mansfield® Limited Lifetime Warranty
- Available in White, Biscuit, and Bone

*Meets ADA height requirement when installed with a regular toilet seat



MODEL 137-3173

Toilet seat not included

Available as CTK



ELONGATED



SMARTHEIGHT ADA



CTK

COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS
137-3173 (K13700073)	Elongated front, ADA*, SmartHeight two-piece toilet.	 HIGH EFFICIENCY TOILET  C  WaterSense MADE IN JAPAN EPA COMPLY  ADA COMPLIANT
137 (137210040)	Elongated front, ADA*, SmartHeight toilet bowl only. Toilet seat not included. Specify color.	
3173 (317310000)	Tank and cover only with left hand, front-mount, color-match, plastic trip lever. Fluidmaster® anti-siphon pilot fill valve. Supply not included. Specify color.	
TANK TRIM & REPLACEMENT PARTS		
31	Trip lever - color-match, plastic trip lever, left hand	
228	3-2" Hybrid flapper flush valve	
400A	Fluidmaster® anti-siphon pilot fill valve	
2206	Anti-siphon pilot fill valve (compatible replacement)	
630-0207	3" Replacement flapper kit	
160-LID	Tank lid	

137-3173 (K13700073)

ALTO® 1.28



Elongated Front, SmartHeight Vitreous China, Two-Piece Toilet

SPECIFICATIONS

MODEL #	DESCRIPTION	CODES/STANDARDS
137-3173 (K13700073)	Elongated front, SmartHeight (1.28 gpf / 4.8 lpf) two-piece toilet	

MATERIAL	Vitreous China
WATER PRESSURE RANGE	20 to 80 PSI
FLUSH SYSTEM	3-2" Hybrid flapper flush valve
WATER USAGE	1.28 gpf / 4.8 lpf
WATER SURFACE AREA	9" X 10"
ROUGH-IN	12"
MaP RATING	800 grams

TRAP DIAMETER	2"
TRAP SEAL	2-5/8"
SHIPPING WEIGHT	Model 137 - 56 lbs. (24 kg) Model 3173 - 34 lbs. (15 kg)
WARRANTY	Vitreous China - Limited Lifetime Tank Trim - Limited One Year

TANK OPTIONS	TECHNICAL INFORMATION
	Note: these dimensions are nominal and subject to change without notice.
3173 Standard 1.28 gpf configuration: 3-2" hybrid flapper flush valve, Fluidmaster® anti-siphon pilot fill valve, left hand, color-match trip lever. 3173RH Variation of model 3173, with right hand, color-match trip lever. 3165 Variation of model 3173, with cover lock. 3174 Variation of model 3173, with tank liner. 3120 Variation of model 3173, with left hand, chrome trip lever. 3125 Variation of model 3173, 14" rough-in.	PLAN VIEW TOILET FOOT PRINT SIDE ELEVATION FRONT ELEVATION

* TOILET SEAT NOT INCLUDED, DIMENSIONS HERE REPRESENT AN STANDARD TOILET SEAT.

Fixture performance and specifications meet or exceed ASME A112.19.2/CSA B45.1 standards, and other state and local codes.