

ITEM NO. 3781159 / MODEL NO. 5027550000




ESSENCE™ 3666**MANSFIELD®**

66" x 36" x 24", Acrylic, Swirl-Way® Whirlpool

FEATURES

- High gloss, easy-to-clean acrylic with fiberglass reinforcement
- Whirlpool hydromassage system uses fully controllable, high-pressure back and body jets for complete muscle relief
- Hydro-V back jet system with back and body jets
- All jets are directionally and flow adjustable
- Includes two pillows
- Oval model with center drain
- Pre-leveled legs for easy installation
- Integrated dual armrests for bather's comfort
- Dual back jets
- Spacious bathing well designed for two-person comfort
- 10-year limited warranty on acrylic
- Installation: Drop-In
- Available in White

**COMPONENTS**

MODEL #	DESCRIPTION	CODES/STANDARDS
5027550000	66" x 36" x 24" Oval Swirl-Way® Whirlpool. Drain not included.	  
ACCESSORIES		
CAB-	Cable Overflow Drain (White — 1330, Chrome — 1335, Everbrass — 1336, Brushed Nickel — 1337, Oil Rubbed Bronze — 1338, Matte Black — 1339)	
TIP-	Tip Toe Overflow Drain (Chrome — 1335, Everbrass — 1336, Brushed Nickel — 1337, Oil Rubbed Bronze — 1338, Matte Black — 1339)	
SWAPOO	Nailing Flange Kit (includes 14' PVC nailing flange, tacky tape and installation instructions)	



ITEM NO. 3781159 / MODEL NO. 5027550000

ESSENCE™ 3666

MANSFIELD®







66" x 36" x 24", Acrylic, Swirl-Way® Whirlpool

SPECIFICATIONS

MATERIAL	Acrylic, fiberglass reinforced	SOAKING DEPTH	15-1/4'
CONSTRUCTION	Self contained, pre-plumbed whirlpool bath system mounted on pre-leveled base.	NUMBER OF JETS	16
ELECTRICAL REQUIREMENTS	One 120 volt, 20 amp GFCI dedicated circuit. Optional heater: separate 120 volt, 20 amp dedicated circuit.	WATER CAPACITY	70 gal. (min.) / 85 gal. (max)
		FLOOR LOADING WEIGHT	47 lbs. sq.ft.
		SHIPPING WEIGHT	Model 5027550000 - 170 lbs. (77 kg)
		WHIRLPOOL PUMP	9 amp
		WARRANTY	Acrylic - 10-Year

TECHNICAL INFORMATION

Note: these dimensions are nominal and subject to change without notice.



NOTES:

1. Pump locations shown for clarity. Specify when ordering STD - Standard or ALT - Alternate.
2. Required pump motor access is 20" W x 15" H.
3. Measurements may vary 1/4" (+/-)
4. Removable apron is not available for this unit.
5. These dimensions are nominal and subject to change without notice.

