

137-125 ALTO[®] 1.6

MANSFIELD[®]

Elongated Front, ADA, 17", Vitreous China, Two-Piece Toilet

FEATURES

- 3-bolt SmartFasten™ tank-to-bowl connection
- 1.6 gpf / 6.0 lpf low water consumption
- Elongated front SmartHeight™ bowl
- 2" flush tower
- Fluidmaster® anti-siphon pilot fill valve
- 14" rough-in
- Model 40 chrome-plated plastic trip lever
- 2" glazed trapway
- The Mansfield® limited lifetime warranty
- Available in White



MODEL 137-125

Toilet seat not included





ELONGATED



17" ADA

COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS
137-125 (137211740-125010000)	Elongated front, SmartHeight™ two-piece toilet.	 
137 (137211740)	Elongated front, SmartHeight™ toilet bowl only. Less toilet seat. Specify color.	
125 (125010000)	Tank and cover only, with left hand, front-mount, chrome-plated, plastic trip lever. Fluidmaster® anti-siphon pilot fill valve. Less supply.	


TANK TRIM & REPLACEMENT PARTS	
40	Trip lever - chrome-plated, plastic trip lever, left hand
211-1112	Flush tower
400A	Fluidmaster® anti-siphon pilot fill valve
630-0030	Replacement flush valve seal
125-LID	Tank lid (14" Rough-in)

137-125 ALTO[®] 1.6



Elongated Front, 17", Vitreous China, Two-Piece Toilet

SPECIFICATIONS


MODEL #	DESCRIPTION	CODES/STANDARDS
137-125	Elongated front, 17" (1.6 gpf / 6.0 lpf) two-piece toilet	  ADA COMPLIANT

MATERIAL	Vitreous China
WATER PRESSURE RANGE	20 to 80 PSI
FLUSH SYSTEM	2" Flush Tower
WATER USAGE	1.6 gpf / 6.0 lpf
WATER SURFACE AREA	9" X 10"
ROUGH-IN	14"
MaP RATING	800 grams

TRAP DIAMETER	2"
TRAP SEAL	2-5/8"
SHIPPING WEIGHT	Model 137 - 50 lbs. (22.6 kg) Model 125 - 46 lbs. (20.8 kg)
WARRANTY	Vitreous China - Limited Lifetime Tank Trim - Limited One Year

TANK OPTIONS	TECHNICAL INFORMATION
--------------	-----------------------

160	Standard 1.6 gpf configuration: 2" flush tower, Fluidmaster [®] anti-siphon pilot fill valve, left hand, chrome trip lever.
160RH	Variation of model 160, with right hand trip lever.
165	Variation of model 160, with cover lock.
170	Variation of model 160, with tank liner.
172	Variation of model 160, with 2" flapper flush valve and chrome trip lever.
173	Variation of model 160, with 2" flapper flush valve and color-match trip lever.
173RH	Variation of model 173, with right hand trip lever.
174	Variation of model 173, with tank liner.
175	Variation of model 160, with cover lock and tank liner.
180	Variation of model 60, with color-match trip lever.
190	Variation of model 160, with color-match trip lever and tank liner.
125	Variation of model 160, with 14" rough-in.



Fixture performance and specifications meet or exceed ASME A112.19.2/CSA B45.1 standards, and other state and local codes.

(152 MM)